

## PRECAST CONCRETE STAIRS + STAIR CLADDING

Handcrafted precast concrete treads, tread + riser units, and cladding. Using GFRC or standard reinforcing, our stairs are completely customizable and work well with various substrates. They can be matched to our other concrete finishes, including floors and walls, to achieve a cohesive design.

## PRODUCT INFORMATION

- Precast concrete
- Suitable for indoor + outdoor use
- · Nine standard colors
- Factory sealed
- Engineering available
- Typical lead time 8-10 weeks
- Template required
- Qualifies for LEED v4
- 5 year structural warranty

STRENGTH	THICKNESS	SIZE	WEIG	HT	JOINTS	ABSORPTION
Compressive: 6,000 psi	11/2"	Up to 8' per piece	19 lbs at 1 1/	per sf	3/16" - 1/4"	6.50%
Flexural: 1,700 psi		DYNAMI COEFFIC	_			
Tensile: 750 psi	FREEZE/THAW	OF FRIC	TION	DIMEN	SIONAL TOLI	ERANCES
	Pass	.56 Wet		Overall: ±1/8"  Angular deviation of plane of side: 1/16"  Warp (out of plane): 1/8" per 5'  Thickness + zero, minus 1/16"		



121 Washington Street Poughkeepsie, NY 12601 845.452.3988 / 212.414.1620

