



## PRECAST CONCRETE TILE

Streamlined and striking, our precast concrete tile lend effortless style to any space. Completely customizable and versatile, they fit right in whether featured in a spacious lobby, airy kitchen, or small washroom.

### PRODUCT INFORMATION

- Precast concrete
- Suitable for indoor use
- Nine standard colors
- Factory sealed
- Typical lead time 8-10 weeks
- Custom sizes + finishes available
- Qualifies for LEED v4
- 5 year structural warranty

### STANDARD PRODUCT DATA

STRENGTH	THICKNESS	SIZE	WEIGHT	JOINTS
Compressive: 6,000 psi	3/4"-1"	24"-48" square	9 lbs per sf	3/16"-1/4"
Flexural: 1,700 psi	DYNAMIC COEFFICIENT OF FRICTION		DIMENSIONAL TOLERANCES	
Tensile: 750 psi	.56 Wet		<ul style="list-style-type: none"> <li>• Overall: <math>\pm 1/8"</math></li> <li>• Angular deviation of plane of side: <math>1/16"</math></li> <li>• Warp (out of plane): <math>1/8"</math> per 5'</li> <li>• Thickness + zero, minus <math>1/16"</math></li> </ul>	

### MANUFACTURING + OFFICE

121 Washington Street  
Poughkeepsie, NY 12601  
845.452.3988 / 212.414.1620

# GRS

GRS is a certified Women-Owned Business (WBE)

[GETREALSURFACES.COM](http://GETREALSURFACES.COM)